

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/085304 A1

(51) International Patent Classification⁷: **B67B 3/20**

FABBRI, Claudio [IT/IT]; Via Scandellara 9, I-40138 Bologna (IT).

(21) International Application Number:
PCT/IB2004/001051

(74) Agent: DALL'OLIO, Giancarlo; Invention S.a.s., Via delle Armi 1, I-40137 Bologna (IT).

(22) International Filing Date: 24 March 2004 (24.03.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
BO2003A000170 27 March 2003 (27.03.2003) IT

(71) Applicant (for all designated States except US): I.M.A. INDUSTRIA MACCHINE AUTOMATICHE S.p.A. [IT/IT]; Via Emilia 428-442, I-40064 Ozzano Emilia (IT).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

(72) Inventors; and

(75) Inventors/Applicants (for US only): SERVADEI, Giovanni [IT/IT]; Via Lacchini 128, I-48018 Faenza (IT).

[Continued on next page]

(54) Title: A METHOD AND A DEVICE FOR CONTROLLED CLOSING OF CONTAINERS WITH THREADED CAPS



(57) Abstract: According to a method for controlled closing a container (1) with a related threaded cap (3), a container (1) is moved to a cap (3) feeding station, where a cap (3) is placed on the threaded upper end of the container (1). Then the container (1), together with the cap (3) is transferred to a closing station, where said cap (3) is screwed to said container (1). During screwing, the instant value of the torque applied to said cap (3) is measured and compared with a pre-selected threshold value, so as to verify, in relation to the threshold value having been reached and to the moment, in which the value is reached, a stable tightening if the cap (3) onto the container (1).



GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments*

Published:

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*